




Relax It's Rheem®



NEW IMPROVED Rheem water heaters with special features to ensure the heater is *much* safer, more reliable and works longer..

- Exclusive Rheemglas enamel tank protection against corrosion by coating the inner tank with an exclusive Rheemglas and fused with solid steel at 870°C. The result is a smooth, tough glass-like lining that effectively resists the corrosive attack of hot water chemicals and ensures a longer life span on Rheem heaters. Tank is designed and tested to withstand 2 times the maximum working pressure of 1000kpa.
- UL approved combined temperature and pressure relief (TPR) safety valve provides protection against excessive water pressure.
- Adjustable thermostat with over temperature protection is a safety device that automatically and safely cuts off the power in the event the preset temperature is exceeded, thus prevents scalding by hot water. Thermostat conserves electricity by cutting-off power supply to the heater once it has reached the preset temperature.
- Flanged Incoloy SS sheathed immersion heating element last longer, resist "dry" firing hence more efficient performance. Efficient heat transferring design reduces sediments built-up in tank.
- Sacrificial Anode rod protects the inner tank from corrosion by equalizing aggressive water reaction, ensuring years of trouble free performance.
- Colorbond pre coated steel jacketing coupled with top and bottom assembly without screws, improves weather protection and moisture resistance. Meet Waterproof Standards of IPX1.
- Thicker CFC free polyurethane insulation between inner tank and epoxy coated steel jacket provides maximum heat retention and lower energy consumption.
- Built-in Factory designed sturdy installation bracket with masonry bolts included.
- Compliance to international requirement IEC 60335-2-21 and PSB Certification- SS 146



Model	Tank Capacity		Stainless Steel Element		Operating Weight (Kg)	Heater Dimension		Shipping Weight (Kg)	Shipping Dimension			Current Draw (amps)	Over Current Protection (amps)	Approx. * Heat up Time to 60°C
	USG	Litres	Voltage	(Kw)		Dia(mm)	Ht (mm)		L (mm)	B (mm)	Ht (mm)			
86VP6S	6	25	240	3.0	42	377	460	17	409	409	548	12.5	15	20 mins
86VP10S	10	42	240	3.0	65	461	487	23	493	493	575	12.5	15	34 mins
86VP15S	15	50	240	3.0	74	461	554	24	493	493	642	12.5	15	40 mins
86VP20S	20	75	240	3.0	105	461	764	30	493	493	851	12.5	15	60 mins
86VP30S	30	100	240	3.0	136	461	973	36	493	493	1060	12.5	15	80 mins

* Heat up time is calculated based on a 3kw, incoming temperature of 25°C. All pipe size for inlet and outlet – 3/4" BSP. All single phase.

DEPENDABLE • HIGH PERFORMANCE • ENERGY EFFICIENT

Although out of sight, the Rheem heater keeps on working, 24/7, year after year...

Call now, for a Rheem dealer nearest to you!



Rheem Manufacturing Company (Singapore) Pte Ltd

8 Pandan Crescent, #02-02 Singapore 128464
 Tel (Sales) : (65) 6872 1161
 Tel (Service) : (65) 6872 2043
 Fax : (65) 6872 1151
 Email : rheem@rheemmfg.com.sg
 Website : http://www.rheemmfg.com.sg

Authorised Dealer